

Instructions for use and safety

TEXFORCE frost protection windscreen cover

Universal polyester cover 120-160 x 105 cm with four elastic straps and hooks

Read these instructions in full before first use. Keep them for future reference and pass them to the next user with the product. The cover is intended only for the front windscreen of a parked vehicle.

1 Product identification and intended use

This product is an external frost protection cover for the front windscreen of a parked car. In winter it limits direct frost build-up on the covered surface. In summer the silver side helps reflect some sunlight passing through the windscreen.

The cover has a universal trapezoidal shape. Check suitability by comparing its dimensions with the windscreen of the specific vehicle. Do not use the product while driving or on a vehicle with the engine running.

- Cover dimensions: 120 cm across the top, 160 cm across the bottom and 105 cm high.
- Side flap length: approximately 24 cm.
- Length of elastic fastening straps with hooks: approximately 60 cm.
- Country of manufacture: China.

2 Materials and set contents

The cover is made of polyester. The black outer side is water-resistant, while the soft silver polyester layer is intended to face the windscreen.

- Cover with side flaps and loops for the mirrors.
- Four elastic straps ending in hooks.
- Storage bag.
- Plastic bag used as product packaging.

3 Packaging warning

- The plastic bag may cause suffocation. After unpacking, immediately keep it away from babies and children.
- Do not allow children to play with the bag and never place it over the head. The bag is not a toy.
- After unpacking, dispose of the bag in the appropriate waste stream in accordance with local sorting rules.

4 Preparation and fitting

Fit the product only to a parked vehicle with the engine switched off and the parking brake applied. Choose a safe location away from traffic. Before fitting, inspect the cover, seams, elastic straps and hooks.

- Clean and dry the windscreen and the side of the cover that touches it. Remove sand, ice and hard debris that could scratch the surface.
- Centre the cover on the windscreen with the black side facing outwards and the soft silver side against the glass.
- Place the loops over the mirrors and position the side flaps between the doors and door frames. Close the doors slowly and make sure the material does not obstruct the lock or seal.
- Attach the hooks to stable points at the wheel rims or wheel arches. Do not attach them to lines, brakes, suspension, sensors, moving parts, sharp edges or hot components.
- Tension the elastic straps evenly. Do not overstretch them or point a tensioned hook towards the face or eyes.
- After fitting, check the stability of the cover and the position of every fastening.

5 Safe use

- Remove the cover, elastic straps and hooks completely before starting the vehicle. Never drive with the cover fitted to the windscreen.

- Do not use the product if the cover, seams, elastic straps or hooks are worn, cracked, deformed or loose.
- Keep control of each tensioned elastic strap while fitting and removing the cover. Sudden release may cause the hook to strike a person or object.
- Do not fit or remove the product in strong wind if the cover and fastenings cannot be controlled safely.
- Keep the product away from open flames, the exhaust system and other sources of high temperature.
- The product is not a toy. Keep the elastic straps, hooks, storage bag and plastic packaging bag out of the reach of children.
- Do not use the cover as a transport tarpaulin, load restraint or cover while towing a vehicle.

6 Winter and summer use

In winter, fit the cover to a clean and preferably dry windscreen. Moisture trapped between the glass and the cover may freeze. If the cover freezes to the windscreen, do not pull it off by force or use sharp tools. Wait for it to thaw or use a safe windscreen defrosting method approved by the vehicle manufacturer.

In summer, the silver surface may reduce heating of the interior, but it does not maintain a safe temperature in the cabin. Never leave children, animals or dependent persons in a parked vehicle.

7 Cleaning maintenance and storage

- Remove light dirt with a soft damp cloth.
- For heavier soiling, wash by hand with a mild detergent.
- Do not use bleach, solvents or aggressive cleaning agents.
- Dry the cover, elastic straps and storage bag thoroughly after cleaning and before reuse or storage.
- Store the product in a dry, ventilated place away from open flames and sources of high temperature.
- Regularly inspect the seams, loops, elastic straps and hooks. Stop using a damaged product.

8 Damaged product and disposal

Stop using the product immediately if damage could cause a hook to detach, an elastic strap to break or the fastening to become unstable. Do not make temporary repairs to components that remain under tension.

Dispose of the worn product, storage bag and plastic packaging bag in the appropriate waste streams in accordance with local sorting rules. Do not burn the product or packaging.

9 Reporting safety issues

In the event of an accident, injury or a defect that may present a hazard, stop using the product immediately. Keep the product, packaging and any available markings, then contact the manufacturer. Provide a description of the incident, the place and date of purchase and any available product identification information.

Economic operator details

Manufacturer
 TEXCORP Sp. z o.o.
 Głogowska 31/33
 60-702 Poznań, Poland
 E-mail: office@texcorp.pl
 Phone: +48 728 976 693