

Instructions for use and safety

Texforce half car cover for windows and roof

All size variants with the same construction and fastening method

Read these instructions in full before first use and keep them for future reference. The product is intended only to cover the windows and roof of a parked car. Always remove the cover and all fastenings completely before driving.

1 Product identification and intended use

The Texforce half cover is intended for temporary protection of all windows and the roof of a parked passenger car. It helps protect the covered surfaces against rain, snow, frost and ice, while the silver surface reflects some sunlight and helps reduce heating of the vehicle interior.

These instructions apply to all size variants made from the same materials and fitted with the same fastening system. Select the correct size for the dimensions and shape of the vehicle according to the variant marking on the product or packaging.

- Brand: Texforce.
- Main material: 100% polyester.
- Vehicle-facing layer: soft non-woven layer intended to protect the paintwork.
- Fastening: eight elastic straps, outer straps with hooks and centre straps joined with a buckle.
- Additional elements: reflective strips on the mirror covers.
- Country of manufacture: China.

2 Important warnings

- The plastic bag presents a suffocation hazard. After unpacking, immediately keep it out of the reach of children. Do not allow children to play with the bag and never place it over the head. The bag is not a toy.
- Do not use the cover while driving, towing the vehicle or running the engine. Remove the cover and all fastenings completely before moving the vehicle.
- Fit and remove the product only when the vehicle is parked securely, the engine is switched off, the parking brake is applied and the bodywork and exhaust system have cooled down.
- Do not go under the vehicle or raise the vehicle to install the straps. Pass components beneath the car from the side of the vehicle.
- Do not attach hooks or straps to brake or fuel lines, the exhaust system, moving parts, sharp edges or parts that may become hot.
- Elastic straps can recoil suddenly. Hold the hook securely while tensioning, never point it towards your face or another person, and release the tension gradually.
- The product is not a toy. Do not allow children to play with the cover, straps, hooks or buckle because of the risk of entanglement and injury.
- Keep the product away from open flames, sparks and sources of high temperature.
- Reflective strips improve the visibility of the covered vehicle but do not replace required lights, markings or safe parking rules.

3 Preparation for fitting

- Check that the selected variant matches the dimensions and shape of the vehicle. A cover that is too small or excessively tensioned straps may damage the product or come loose during use.
- Remove sand, ice, twigs and other hard or sharp debris from the vehicle body and the cover. Moving such debris across the paintwork may cause scratches.
- Before every use, inspect the fabric, seams, straps, hooks and buckle. Do not use the product if any fastening component is cracked, cut, permanently stretched or loose.
- Do not fit the cover to a freshly painted vehicle before the curing period specified by the paintwork contractor has elapsed.

4 Fitting the cover

- Unfold the cover and position it with the soft non-woven layer facing the vehicle.
- Place the cover over the roof and windows without dragging it forcefully across the paintwork. Fit the mirror covers over the mirrors.
- Align the cover so that it lies evenly and does not obstruct the points where the straps will be attached.
- Attach the outer straps with hooks to stable points at the wheel rims where the hook will not damage the surface or contact brake components.

- Pass the centre straps beneath the vehicle from one side to the other without going under the vehicle, then connect the buckle.
- Tension the straps evenly. Do not stretch them to their limit or twist them.
- After fitting, check every attachment point. The cover must not contact hot, sharp or moving vehicle components.

5 Safe use

- Use the cover only for its intended purpose and only on a parked vehicle.
- Check the position of the product and the tension of the straps regularly, particularly after a change in weather.
- In strong or gusty winds, remove the cover if secure attachment cannot be ensured.
- Do not allow a heavy layer of wet snow to remain on the cover for a prolonged period. Remove accumulated snow carefully without using sharp tools.
- Do not pull the cover off suddenly if it has frozen to the vehicle. Wait for the ice layer to loosen and remove the material gradually.
- Do not use the cover for lifting, towing, securing loads or any purpose other than covering the windows and roof of a car.
- Do not modify the straps, hooks, buckle or cover construction.

6 Removing the cover

- Before releasing the fastenings, make sure that no person nearby could be struck by a hook or tensioned strap.
- Release the centre buckle first while controlling the tension of the straps, then detach the outer hooks one by one.
- Remove the material by lifting and folding it. Do not drag it over a dirty vehicle surface.
- Before starting the engine, check that the cover and all straps and hooks have been completely removed from the vehicle and its surroundings.

7 Cleaning and inspection

Remove light dirt with a damp cloth. The cover may be washed by hand when necessary. After cleaning, allow it to dry completely before folding or refitting.

- Do not clean the cover while the engine is running or near hot vehicle components.
- After cleaning, inspect the seams, non-woven layer, straps, hooks and buckle.
- Stop using the product if damage could weaken the fastening system or expose parts that may scratch the vehicle.

8 Storage

- Store the cover clean and completely dry.
- Choose a dry location away from open flames, sparks and sources of high temperature.
- Secure the straps and hooks against tangling and accidental snagging.
- Keep the product out of the reach of children.

9 Damaged or end of life product

Do not use a cover with a damaged fastening system, extensive tearing or an exposed component that could damage the vehicle. Dispose of the worn product and plastic bag in the appropriate waste stream in accordance with local sorting rules. Do not burn the product or packaging.

10 Reporting safety issues

In the event of injury, an accident or a defect that may present a hazard, stop using the product immediately. Keep the product, packaging and variant marking, then contact the manufacturer with a description of the incident and any available identification information.

Economic operator details

Manufacturer

TEXCORP Sp. z o.o.
 Głogowska 31/33
 60-702 Poznań, Polska
 E-mail: office@texcorp.pl
 Phone: +48 728 976 693